LSST Sensor Characterization with Ultraflats

Michael Baumer and Aaron Roodman








Introduction


With the great promise of LSST science come unprecedented demands on camera performance—sub-percent photometry and ellipticities good to a few parts in a thousand. These demands make it necessary to investigate heretofore unconsidered sources of systematic errors within the LSST camera.

One possible source of these errors comes from small-scale variations in pixel sensitivity, classically referred to as pixel response non-uniformity (PRNU). It has previously been assumed that the dominant contribution to PRNU comes from **local variation in the quantum efficiency (QE)** of a pixel within a CCD sensor. However, more recent work [1,2] has indicated that **lateral electric fields** produced by impurities within the silicon bulk of a CCD can also contribute to PRNU.





To investigate these effects in an e2v-250 LSST prototype sensor (112-03), we constructed "ultraflat" images by combining 500 flat-field exposures at four different light levels taken by the Harvard sensor testing lab.

Shot noise contamination decreases with number of coadded images as expected, but what are the causes of the residual variance (PRNU)?



Single-pixel Photon Transfer Photon transfer curves (PTCs) are commonly used to characterize the performance of CCDs. With ultraflats, we can perform a linearity (signal vs. time) and PTC (variance vs. signal) analysis on a pixel-by-pixel basis: 100ke- Ultraflat Pixel Linearity PTC Slope Though no Sample PTCs for 200 pixels patterns are discernible in the 20000 raw ultraflat or linearity map, certain columns exhibit lower variance at high light level (but still below fullwell). Mean Signal (ADU) — 1st Overscan Missing variance is associated unexpected charge in first overscan row. One possible explanation is a flux-dependent charge transfer inefficiency, but what would be the physical mechanism? Why is the effect localized to particular columns?





Conclusions and Future Work

Ultraflats are useful probes of pixel geometry in CCD sensors. We have used them here to probe linearity, noise, and sensitivity properties at pixel-level scale, and have observed apparent variations in pixel size in an LSST prototype sensor. Efforts to create a model for these effects (which would allow full decoupling of PRNU contributions from pixel size variation and local QE variation) are ongoing, with the goal of improving the procedure of naïve flat-fielding. We also plan to take images sinusoidal illumination fields, which have the potential to allow improved characterization of pixel size variation in our test device.

Acknowledgments + References

[1] Stubbs 2014 JINST 9: C3032[2] Smith 2008 SPIE Conf. Ser. 7021

Thanks to Peter Doherty and Chris Stubbs for useful discussions and providing flat-field data. M. Baumer is supported by an NSF Graduate Research Fellowship.